



Boiler Model	No. of 50kW Modules	Output		Shipping Weight (kg) approx.	Flow & Return Flanges BS 4504 PN6	Gas Connections	No. of Compact Casings
		kW	Btu/h x 1000				
Compact 50	1*	50	171	90	32	Rc1/2"	1
Compact 100	2	100	341	165	32	Rc1/2"	1
Compact 150	3*	150	512	255	50	R1"	2
Compact 200	4	200	682	330	50	R1"	2
Compact 250	5*	250	853	420	80	R1"	3
Compact 300	6	300	1024	495	80	R1"	3
Compact 350	7*	350	1195	585	80	R1 1/4"	4
Compact 400	8	400	1365	660	80	R1 1/4"	4
Compact 450	9*	450	1536	750	80	R1 1/4"	5
Compact 500	10	500	1706	825	80	R1 1/4"	5
Compact 550	11*	550	1876	915	80	R1 1/4"	6
Compact 600	12	600	2047	990	80	R1 1/4"	6

* Includes Compact 100 with one 50kW module blanked off. Multiple units are supplied with interlocking casings.

Installation Clearances

Wessex-HE 50 boilers should be positioned to allow a minimum clearance of 150mm from adjacent walls or equipment, to facilitate inspection. Access will be required to the rear of the boiler for connecting condensate drain pipework.